

**Lexan® Thermoclear®,
Lexan® Thermoclear-Plus®
and Lexan® Thermoclear®
Dripgard Sheet**

**Ten Year
Limited Warranty:**

*Standard Lexan® Thermoclear®,
Lexan® Thermoclear-Plus®
and Lexan® Thermoclear®
Dripgard Sheet will not break
due to loss of impact strength
through weathering and will not
display excessive yellowing and
loss of light transmission as
defined herein, within ten (10)
years of date of sale by GE Plastics.*

This limited warranty is subject to the following conditions :

1. This limited warranty applies exclusively to standard sheet glazing produced by GE Plastics in Europe with a minimum gauge of 6 mm in the colours standard clear (112), standard bronze (515055), opal white (82995), used correctly as sloped, vertical or cold curved glazing, handled, stored, processed, installed and maintained according to GE Plastics' recommendations contained in the Technical Manual. In all cases, the surface bearing the proprietary UV protection must be the only side exposed to direct sunlight and the effects of weather.
 - Loss of light transmission will be determined by subjecting a cleaned sheet sample to the Light Transmission Test ASTM D1003 (1977). Any claims for sheets displaying a loss of light transmission of 2% or less, compared to their original value, will not be accepted.
2. This limited warranty does not apply to sheet that has been thermoformed, scratched, abraded or exposed to corrosive materials or chemicals.
3. Any warranty claim hereunder must be made immediately within the warranty period by specifying the claim in writing and submitting to GE Plastics the original sales receipt which must contain name and address of the purchaser, the date of purchase, the complete product name, the lotnumber and the volume purchased. On request of GE Plastics claimant must allow the material to be inspected on site and/or return the sheet to GE Plastics for testing.
 - Yellowing will be determined by subjecting a cleaned sheet sample to the Yellowness Index Test ASTM D1925 (1977). Any claims for sheets displaying a change in Yellowness Index of 2 Δ or less for standard clear (112) and 5 Δ or less for opal white (82995) and bronze (515055), compared with their original value, will not be accepted.
4. For the purpose of this warranty:
 - Loss of impact strength through weathering leading to hail breakage will be determined by subjecting a sample of the damaged sheet to a standard hail simulation test developed by KRI-TNO, Delft, The Netherlands. Acceptance of a claim under this warranty requires that this test (10 shots with artificial hailstones of 20 mm in diameter aimed at different points of the sheet surface with a speed of 21 m/s) causes at least 5 holes in the weathered surface of the sheet.
5. GE Plastics reserves the right to investigate independently the cause of any failure.
6. If a claim under this limited warranty is justified, GE Plastics will provide the purchaser with replacement material free of charge in accordance with the following schedule:

Time from Orig. Purchase Date	Material Replacement
Up to 5 years	100%
in 6th year	75%
in 7th year	60%
in 8th year	45%
in 9th year	30%
in 10th year	15%

 - If replacement material cannot be provided within a reasonable period of time, GE Plastics may opt to refund the original purchase price paid to GE Plastics, or a portion thereof, in accordance with the above schedule.
7. This limited warranty shall be GE Plastics' sole liability for the products and all other claims for damages are excluded. The limited warranty is in lieu of all other warranties (except of title), written or oral, statutory, express or implied, including any warranty of merchantability or fitness of purpose.

This ten year warranty shall be governed by the laws of the Netherlands.
8. This warranty has been issued on July 1, 2000, is restricted to material sold by GE Plastics after such date and supersedes all previously issued warranties for the products mentioned above.

European Headquarters
General Electric Plastics B.V. SPE
Plasticslaan 1
PO Box 117
NL - 4600 AC Bergen op Zoom
The Netherlands
Tel. (31) (164) 29 27 42
Fax (31) (164) 29 19 86

GE Plastics Ltd.
Old Hall Road
Sale
Cheshire M33 2HG
United Kingdom
Tel. (44) (161) 905 50 01
Fax (44) (161) 905 50 04

General Electric Plastics Italia S.p.A.
Viale Brianza 181
I - 20092 Cinisello Balsamo (Mi)
Italy
Tel. (39) (02) 61 83 42 61
Fax (39) (02) 61 83 42 09

General Electric Plastics GmbH
Eisenstrasse 5
D - 65428 Rüsselsheim
Germany
Tel. (49) (61 42) 60 11 01
Fax (49) (61 42) 60 12 59

GET sl (Gestión y Especificaciones Técnicas)
Agente Oficial España y Portugal
G/Girona, 67, 3º-2a
08009 Barcelona, Spain
Tél. (34) (93) 488 03 18
Fax (34) (93) 487 32 36

General Electric Plastics France S.à.R.L.
Z.I. de St. Guénault
B.P. 67
F - 91002 Evry-Cedex
France
Tel. (33) (1) 60 79 69 00
Fax (33) (1) 60 79 69 21

Lexan® Thermoclear® and Thermoclear-Plus®
are registered trademarks of the General Electric Co.,
USA, which is not connected with the English
company of a similar name.



GE Structured Products

**Lexan® Thermoclear®
Sheet**

**Lexan® Thermoclear-
Plus® Sheet**

**Lexan® Thermoclear®
Drippard Sheet**

**Ten Year
Limited
Warranty**

Lexan



GE Structured Products

www.gestructuredproducts.com